

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Metal-working product
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160

NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

H229 Pressurised container: May burst if heated.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

GB-EN

(Contd. on page 2)

www.griffon.eu 1/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Metal working product

Dangerous components:			
CAS: 10024-97-2	dinitrogen oxide	1-2.5%	
EINECS: 233-032-0	♠ Ox. Gas 1, H270; ♦ Press. Gas (Liq.), H280; ♦ STOT		
Reg.nr.: 01-2119970538-25	SE 3, H336		
CAS: 137-16-6	sodiumlaurylsarcosinate	<1%	
Reg.nr.: 01-2119527780-39	Acute Tox. 2, H330; 鉖 Eye Dam. 1, H318; 🕔 Skin Irrit. 2, H315		

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

- GB-EN

www.griffon.eu 2/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 2)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

10024-97-2 dinitrogen oxide

WEL Long-term value: 183 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Not required.

GB-FN

(Contd. on page 4)

www.griffon.eu 3/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 3)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· Melting point/freezing point: 0 °C

· Boiling point or initial boiling point and

boiling range 100 °C

· Flammability Not applicable.

Lower and upper explosion limit

• **Lower:** 2.6 Vol % • **Upper:** 12.6 Vol %

· Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 0.952 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure at 20 °C: 23 hPa

Vapour pressure at 20 °C:
Density and/or relative density

Density at 20 °C:

Relative density

1.04 g/cm³

Not determined.

• **Vapour density** Not determined. Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Aerosol

Important information on protection of health

and environment, and on safety.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent content:

· Water: 98.4 %
 · Solids content: 0.3 %
 · Molecular weight 18.02 g/mol

Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 5)

- GB-EN

www.griffon.eu 4/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 4)

	(Contd. or page 4)
· Flammable gases	Void
· Aerosols	Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

10024-97-2 dinitrogen oxide

Inhalative LC50/4 h 1.06 mg/l (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB-FN

www.griffon.eu 5/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 5)

- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Not hazardous for water.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number	LINIAOEO	
ADR/ADN, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR/ADN	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, non-flammable	

www.griffon.eu 6/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.02.2023 Version number 33 (replaces version 32) Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR/ADN · Class 2 5A Gases. · Label 2.2 · IMDG. IATA 2.2 Gases. · Class · Label 22 · 14.4 Packing group · ADR/ADN, IMDG, IATA not regulated · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -· EMS Number: F-D,S-U SW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity Segregation Code of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: **Quantity limitations** On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

www.griffon.eu 7/9

1L

(Contd. on page 8)

GB-EN

ADR/ADN

Limited quantities (LQ)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 33 (replaces version 32) Revision: 18.08.2022 Printing date 11.02.2023

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

-				-
ıι . ω	ntd	Λt	page	

	(Contd. of page 7)
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	3
· Tunnel restriction code	E
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III.
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**
- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H270 May cause or intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)

GB-EN

8/9 www.griffon.eu



Safety data sheet according to 1907/2006/EC, Article 31

Version number 33 (replaces version 32) Printing date 11.02.2023 Revision: 18.08.2022

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 8)

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Aerosols, Section 2.3.1 Bridging principles

Department issuing SDS: Bison QESH

· Contact: Reach coordinator

Date of previous version: 04.07.2022 · Version number of previous version: 32

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 3: Aerosols – Category 3 Ox. Gas 1: Oxidizing gases – Category 1

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Acute Tox. 2: Acute toxicity - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* * Data compared to the previous version altered.

GR-FN

www.griffon.eu