

ELBEblue line® FLEECE ADHESIVE

Ready-to-use, water-based adhesive dispersion based on synthetic resin

suitable for the bonding of polyester fleece

Technical Data

Essential characteristics	Performance	
Appearance	White dispersion	
Viscosity	ca. 30.000 mPas	
Dry content	ca. 60 %	
Density	ca. 1 g/cm ³	
pH value	3,5-4,5	
Open time	ca. 15 min.	

Storage

Store dry, cool and frost-free in tightly-closed original containers for approx. 6 months between + 15 °C and + 20 °C.

Application temperature

Ambient air and surface must be at least + 5 °C during application and drying.

Application

Before using the adhesive it must be stirred. A thin adhesive film is applied to one of the two adhesive surfaces using a brush, roller, steel blade or a flat toothed spatula. The opaque or less absorbent substrate should be selected for the application of the adhesive. Joining may be immediate, but should be done within the open time of 15 minutes. The applicators are to be cleaned immediately with water after use, since dried adhesive is hardly removable.

Ingredients

Acrylate dispersion, water, additives, preservative (DCOIT)

Safety instructions

Keep out of reach of children. Avoid eating, drinking and smoking when using the product. Ensure good ventilation during and after application. Take off soiled clothing. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains, water courses or soil. Toxic to aquatic organisms, long-term effect. Contains: 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT). May cause an allergic skin reaction.

Waste disposal

Only containers free from residues can be recycled. Dried material residues can be disposed of with the normal household waste or with construction waste. Liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.

Legal notice

The customer/installer has to check the applicability of the product for the intended use. He is responsible for the proper application, usage and processing of the product.

We assure the correct quality of our products according to our conditions of sale and delivery.
All declarations comply with our recent knowledge.



ELBTAL PLASTICS GmbH & Co. KG
Grenzstraße 9, 01640 Coswig, GERMANY
Phone: +49 (0) 3523 5330 0
Fax: +49 (0) 3523 5330 220
www.elbtal-plastics.de

Rev. 00, 20.04.2017
This data sheet replaces all previous data sheets.