

LPD FOR STANDS



Applications:

- Prevents drainage from the irrigation system on start up and shut down
- Maintains a full irrigation system and ensures uniform irrigation in each area at a given time
- Contributes to efficient irrigation, high-quality peak yields and significant savings of water and fertilizers
- Prevents destruction of crop rows (raised beds) and damage to bulb and root crops caused by exposure to light

Structure and features

- High flow design at minimum head losses
- Durable plastic, resistant to breakage, radiation and fertilizers
- Used as an adaptor for Stand 52 (F $\frac{1}{2}$ x 12 barb)
- Connects to Elite stands and $\frac{1}{2}$ " and $\frac{3}{4}$ " risers
- Recommended working pressure: 2-4 bar

TECHNICAL DATA

Discharge (l/h)	Opening pressure (m)	Closing pressure (m)	Head loss (m)
up to 750	11.0	6.0	0.8
750-1500	14.0	8.0	2.6

LPD (Leakage Prevention Device)



PRODUCT RANGE

Description	Catalog no.	
Adaptor for IrriStand 52, 53	482820	
IrriStand 52 LPD barb 12 mm	790512	
IrriStand 56 LPD barb 16 mm	790516	
Universal 1/2" LPD (for Elite)	790601	
Universal 3/4" x 1/2" LPD (for Elite)	790602	