

ClickTif HD Accessories



DROP GUIDE

Use as single outlet for drop guide

LABYRINTH STAKES

Can be used as an independent dripper or to stabilize flow rate at multiple outlets

When working with multiple outlets:

- 1. Use labyrinth stakes to improve uniformity
- 2. Minimum recommended working pressure: I bar
- 3. Maximum recommended flow per outlet: 2.0 l/h
- 4. Minimum recommended flow per outlet:
- Flat surface and uniform tube length 0.5 l/h
- On a slope or uneven elevation I.0 l/h

Recommended combinations:

Number of	Dripper flow rate I/h					
outlets	1.3	2	3	4	8	12
2	•	•	•		-	-
3	-	•	•	•	-	-
4	-	•	•	•	٠	-
5	-	-	•	•	•	-
6	-	-	•	•	•	•

- Only on flat surface and with uniform tube length
- For all conditions, including slopes and uneven elevations

FLOW RATE VS. PRESSURE

TEOWNATE VS. I RESSORE							
	Flow rate (I/h)						
Pressure (m)	Elbow labyrinth stake Catalog no. 802850	Straigt labyrinth stake Catalog no. 802800					
5	1.5	1.6					
10	2.0	2.3					
15	2.5	2.8					
20	3.5	3.2					

3/5 mmoutlet connectors



802908 802920 802940

2, 4, 8 outlets with flow control stakes

Multi-level connectors



Catalog no. 802928

Catalog no. 802948

2.5 mm Punch

Special design for comfortable punching and inserting of ClickTif drippers



Catalog no. 897284

