

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 28 Printing date 19.06.2021 Revision: 14.06.2021

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: GRF WDF-05 BO 500ML\*12 L193
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

**Bison International** 

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

(Contd. on page 2)

GB-EN

1/11 www.griffon.eu



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 1)

#### · Signal word Danger

#### · Hazard-determining components of labelling:

tetrahydrofuran

butanone

#### · Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P281 Use personal protective equipment as required.

P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

### · Hazard pictograms







GHS02 GHS07 GHS08

#### · Signal word Danger

#### · Hazard-determining components of labelling:

tetrahydrofuran

butanone

#### · Hazard statements

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P281 Use personal protective equipment as required.

P501 Dispose of contents/container in accordance with national regulations.

#### 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB-EN -

(Contd. on page 3)

www.griffon.eu 2/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 2)

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Adhesive

Dangerous components:			
CAS: 109-99-9 EINECS: 203-726-8 Index number: 603-025-00-0 Reg.nr.: 01-2119444314-46	tetrahydrofuran  Flam. Liq. 2, H225; Carc. 2, H351; Eye Irrit. 2, H319; STOT SE 3, H335	50-100%	
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone  Flam. Liq. 2, H225; Use Irrit. 2, H319; STOT SE 3, H336	25-50%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

(Contd. on page 4)

GB-EN

www.griffon.eu 3/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

### 109-99-9 tetrahydrofuran

WEL Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm

Sk

(Contd. on page 5)

GB-EN

www.griffon.eu 4/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

		(Contd. of page 4)		
78-93-3 butanone				
WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm				
	Sk, BMGV			
· DNELs	· DNELs			
78-93-3 butanone				
Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day		
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day		
Inhalative	Inhalative Consumer, inhalation, longterm exposition 106 mg/m³			
· PNECs				
78-93-3 butanone				
Fresh water 55.8 mg/l				
Marine wa	ırine water 55.8 mg/l			
Soil	22.5 mg/kg			
Ingrediente with historieal limit values.				

#### Ingredients with biological limit values:

#### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

#### · Recommended filter device for short term use: Filter A

#### · Protection of hands:

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

Butyl rubber, BR

Recommended thickness of the material: > 0,7 mm

(Contd. on page 6)

(Contd. of page 4)

GB-EN

www.griffon.eu 5/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 5)

#### · Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye protection:



Tightly sealed goggles

Goggles recommended during refilling

**Body protection:** Solvent resistant protective clothing

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

**Colour:** According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 65.5 °C

· Flash point: -21 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 230 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol % Upper: 12 Vol %

· Vapour pressure at 20 °C: 200 hPa

Density at 20 °C: 0.965-0.966 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 7)

GB-EN

www.griffon.eu 6/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

	(Contd. of page 6)
· Viscosity:	
Dynamic at 20 °C:	675 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	83.1 %
Water:	0.0 %
Solids content:	16.9 %
· 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
109-99-9 tetrahydrofuran			
Oral	LD50	2500 mg/kg (rat)	
78-93-3 butanone			
Oral	LD50	3300 mg/kg (rat)	
Dermal	LD50	5000 mg/kg (rabbit)	

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.

(Contd. on page 8)

GB-EN

www.griffon.eu 7/11



## Safety data sheet according to 1907/2006/EC, Article 31

Version number 28 Revision: 14.06.2021 Printing date 19.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 7)

· Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Disposal must be made according to official regulations.

- Uncleaned packaging:
- **Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR/ADN, IMDG, IATA

UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES IMDG, IATA **ADHESIVES** 

(Contd. on page 9)

8/11 www.griffon.eu



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR/ADN



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG. IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): -

EMS Number: F-E,S-D

· Stowage Category A

14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

Quantity limitations

On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

· ADR/ADN

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· Transport category 3 · Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

ml

• Remarks: Under certain conditions substances in Class 3

(flammable liquids) can be classified in

packinggroup III.

(Contd. on page 10)

- GB-EN

www.griffon.eu 9/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 9)

	(Serial of page 5)
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
, , ,	The classification of the mixture is generally based
,	on the calculation method using substance data
Specific target organ toxicity (single exposure)	according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Bison QESH

· Contact: Reach coordinator

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 11)

- GB-EN

www.griffon.eu 10/11



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2021 Version number 28 Revision: 14.06.2021

Trade name: GRF WDF-05 BO 500ML\*12 L193

(Contd. of page 10)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB-EN

www.griffon.eu 11/11