

BUBBLERS



BUBBLERS

PCB-25-**R**
PCB-50-**R**
PCB-10-**R**
PCB-20-**R**

Bubblers Key

25 - 0.9 l/min 10 - 3.8 l/min
50 - 1.9 l/min 20 - 7.6 l/min

VALVES



ICV

ICV-101G-FS-**R**
ICV-151G-B-FS-**R**
ICV-201G-B-FS-**R**
ICV-301-FS-**R**
561205 = ICV-101-201 series
ID handle
515005 = ICV-301 series
ID handle



IBV

IBV-101G-FS-**R**
IBV-151G-FS-**R**
IBV-201G-FS-**R**
IBV-301G-FS-**R**



QUICK COUPLER

HQ-33DLRC-**R**
HQ-44LRC-**R**
HQ-44LRC-AW-**R**
HQ-5LRC-**R**
HQ-5LRC-BSP-**R**

Quick Coupler Key

LRC - Locking rubber cover
RC - Rubber cover
AW - Acme key with
anti-rotation wheels

Valves Key

B - BSP threads
FS - Filter Sentry™
LRC - Locking rubber cover
RC - Rubber cover
AW - Acme key with anti-rotation wheels

* **Note:** IBV purple tags are user-installed options.

MICRO



IH RISERS

IH-RISER-XX-**R**
IH-XX-YY-CV-**R**
IH-FIT-3850-**R**



RZWS

RZWS-10-**R** RZWS-36-**R**
RZWS-10-25-**R** RZWS-36-25-**R**
RZWS-10-50-**R** RZWS-36-50-**R**
RZWS-10-25-CV-**R** RZWS-36-25-CV-**R**
RZWS-10-50-CV-**R** RZWS-36-50-CV-**R**
RZWS-18-**R** 913301SP
RZWS-18-25-**R** (purple cap for
45 cm and 90 cm)
RZWS-18-50-**R** RZWS10-RCC
RZWS-18-25-CV-**R** (purple cap for
25 cm)
RZWS-18-50-CV-**R**



HDL

HDL-06-12-250-**R** HDL-09-12-1K-**R**
HDL-06-12-500-**R** HDL-09-18-250-**R**
HDL-06-12-1K-**R** HDL-09-18-500-**R**
HDL-06-18-250-**R** HDL-09-18-1K-**R**
HDL-06-18-500-**R** HDL-09-24-250-**R**
HDL-06-18-1K-**R** HDL-09-24-250-**R**
HDL-06-24-250-**R** HDL-09-24-1K-**R**
HDL-06-24-1K-**R** HDL-BLNK-250-**R**
HDL-09-12-250-**R** HDL-BLNK-500-**R**
HDL-09-12-500-**R** HDL-BLNK-1K-**R**



MULTI-PURPOSE BOX

MB-0811-**R**
MB-LID-**R** (lid only)

Micro Key

IH Risers

12 - 30 cm XX - Riser length (15, 30, 45, 61, 91) cm
18 - 45 cm YY - Emitter flow (2, 4, 8, 15, 23) l/hr
24 - 61 cm CV - Check valve (standard)

RZWS

10 - 25 cm 25 - 0.9 l/min
18 - 45 cm 50 - 1.9 l/min
36 - 90 cm CV - Check valve

HDL

BLNK - No emitter HDL-09 - 3.4 l/hr
HDL-04 - 1.5 l/hr 12 - 12 cm
HDL-06 - 2.1 l/hr 18 - 18 cm

24 - 24 cm 1K - 300 m
250 - 75 m
500 - 150 m