


COD. 21.16.16

ELECTROFUSION 45° ELBOW

SDR 11 - PN 16



DIMENSIONS						WEIGHTS	
dn	de	L	f	a	Z		
25	39	33	15	10	55	80	
32	46	39	18	10	57	110	
40	56	48	25	11	70	175	
50	68	54	27	12	75	260	
63	82	52	27	13	86	390	
75	97	64	29	18	98	610	
90	116	70	37	18	110	905	
110	142	76	39	20	114	1415	
125	162	79	42	19	119	1830	
140	177	86	39	20	134	2200	
160	206	89	45	20	134	3400	
180	223	105	50	28	165	4300	
200	250	112	55	29	171	5300	
225	281	120	48	36	185		■
250	310	127	53	33	199		■
315	397	145	51	48	230		■

■ in preparation

_ Moulded in PE 100-RC

_ Absolutely compulsory the use of aligning clamp for all diameters

_ Absolutely compulsory the pipes/fittings scraping


WELDABILITY ON PIPE/FITTING PE 100		
dn	SDR 17	SDR 11
25		● ▲
32	● ▲	●
40	● ▲	●
50	●	●
63	●	●
75	●	●
90	●	●
110	●	●
125	●	●
140	●	●
160	●	●
180	●	●
200	●	●
225	●	●
250	●	●
315	●	●

- weldable only with universal ef units
- weldable only with monovalent welding units Series Euro
- ▲ minimum weldable thickness 3 mm

COD. 21.16.25

ELECTROFUSION 45° ELBOW

SDR 7,4 - PN 25



DIMENSIONS						WEIGHTS	
dn	de	L	f	a	Z		
25	39	33	15	10	55	80	
32	46	39	18	10	57	110	
40	56	48	25	11	70	175	
50	68	54	27	12	75	260	
63	82	52	27	13	86	390	
75	97	64	29	18	98	610	
90	116	70	37	18	110	905	
110	142	76	39	20	114	1415	
125	162	79	42	19	119	1830	
160	206	89	45	20	134	3400	

WELDABILITY ON PIPE/FITTING PE 100				
dn	SDR 17	SDR 11	SDR 9	SDR 7,4
25		● ▲	●	●
32	● ▲	●	●	●
40	● ▲	●	●	●
50	●	●	●	●
63	●	●	●	●
75	●	●	●	●
90	●	●	●	●
110	●	●	●	●
125	●	●	●	●
160	●	●	●	●

- weldable only with universal ef units
- weldable only with monovalent welding units Series Euro
- ▲ minimum weldable thickness 3 mm