

# MULTI-PORT EMITTERS

Use these emitters to irrigate groups of plants effectively from one source.

## KEY BENEFITS

- Six pressure-compensating emitter ports provide consistent and reliable flow
- Colour-coded by flow for easy identification
- Earth-tone colours blend in with surrounding landscape
- Swivel elbows assist in placing water directly to plant
- MPM (Multi-Port Manifold) provides unrestricted flow for each outlet

## PRODUCT SPECIFICATIONS

- Available in ½" FNPT
- Available flows: 2, 4, 8 l/hr
- PVC cap plugs port when not being used

## OPERATING SPECIFICATIONS

- Pressure range: 1.4 to 3.5 bar; 140 to 350 kPa
- Minimum filtration: 150 mesh; 100 microns
- Warranty period: 2 years

### MULTI-PORT EMITTER MODEL CHART

	Model	Flow (l/hr)
● Blue	MPE-05	2.0
● Black	MPE-10	4.0
● Red	MPE-20	8.0
● Grey	MPM-050	N/A



**Multi-Port Emitter**



**Multi-Port Manifold**

(MPM-050)

Unrestricted flow through outlets as indicated by grey colour. Use with 6 mm distribution tubing and a barbed emitter at the end (available in ½" FPT). Allows water to be directed to as many as six different locations.

### Emitter Caps

(MPE-CAPS)

Plug unused 6 mm barbed emitter outlets. Use with Hunter Multi-Port Emitters.



# RIGID RISERS

These risers maintain their stiffness even when used with micro sprays, making them a perfect choice for high-throw applications.

## KEY BENEFITS

- Provide a rigid connection for emitters and micro sprays
- Increase the height of sprays for flower beds

## PRODUCT SPECIFICATIONS

- Inlet configurations: blank, 6 mm barb, ½" FNPT

## OPERATING SPECIFICATIONS

- Pressure range: 1.4 to 4.1 bar; 140 to 410 kPa
- Warranty period: 1 year



**30 cm Rigid Riser**

(also available in 45 cm)

### RIGID RISER MODEL CHART

Model	Description
RR12	30 cm rigid riser
RR12-T	30 cm rigid riser with ½" threaded base
RR12-B	30 cm rigid riser with 6 mm barb base
RR18	45 cm rigid riser
RR18-T	45 cm rigid riser with ½" threaded base
RR18-B	45 cm rigid riser with 6 mm barb base