

6004 SD



Undertree sprinklers

Very low angle (4°), low volume, plastic 1/2" male impact SD sprinkler

Applications: orchards and plantations, especially table grapes and bananas

- 4° low angle facilitates a flat stream, close to the ground, preventing the wetting of foliage.
- Unique hammer with SD (super-diffuser) plate for uniform distribution.
- Special arched water path for maximum coverage diameter.
- Resistance to UV radiation and exterior impact.
- Sprinkler drive mechanism prevents potential damage caused by snails.

6004 SD PERFORMANCE TABLE

Nozzle color (mm)	P (bar)	Q (l/h)	D (m)	MSH* (cm)
2.8 Orange	2.0	480	14.0	25
	2.5	530	15.0	
	3.0	584	16.0	
	3.5	630	17.0	
	4.0	675	17.5	
3.0 Red	2.0	525	14.0	28
	2.5	585	15.0	
	3.0	640	16.0	
	3.5	695	16.5	
	4.0	745	17.0	
3.2 Green	2.0	570	14.5	30
	2.5	640	15.5	
	3.0	700	16.5	
	3.5	765	17.0	
	4.0	815	18.0	

* MSH - Max. Stream Height (from nozzle)

* Performance table prepared under laboratory conditions

* For windy conditions use closer spacing

